## PHILIPPINE SCIENCE HIGH SCHOOL SYSTEM

## **REQUEST FOR QUOTATION FORM & NOTICE**

**GOODS** 

Office/Campus:	PHILIPPINE SCIENCE HIGH SCHOOL-ZAMBOANGA REGION CAMPUS
Address/Contact Details:	Cogon, Dipolog City

	Quotation No.:	2020-10-0204
GENTLEMEN:	Date:	October 21, 2020

May we request for quotation on materials enumerated hereunder. If you are interested and in a position to furnish the same, we shall be glad to have your best prices.

Delivery within \_\_\_\_\_ working days upon receipt of approved Purchase Order (PO).

In case of failure to make the full delivery/completion within the time specified as offered/required, the Supplier/Contractor shall be liable for liquidated damages/penalty of one-tenth (1/10) of one percent (1%) of the Contract Price per calendar day of delay minus the value of the delivered/completed portion(s) of the approved P.O./Contract.

tem#	QTY	UNIT	ITEM/DESCRIPTION	UNIT COST	TOTAL COST
			PRICES MUST BE Tax (VAT) INCLUSIVE		
1	4	roll	305m UTP CAT6; 100 ohm twisted pair copper cable; High Performance		
2	4	pack	Cable Tie 100pcs 200mm(8in.) black		
3	400	pcs	RJ45 CAT6 Pass-through Connector Shielded		
4	400	pcs	RJ45 Network Cable Protector Plug Boots Cap Cover (Blue)		
5	1	pcs	Pass-through Ethernet Crimping Tool		and property
6	30	pcs	PVC Electrical Cable Moulding 25mmx16mmx2440mm (white)		
7	50	pcs	Cable Duct 2in.x2in.x1.8m(gray)		
8	4	pcs	No More Nails Construction Adhesive (320g)		
9	2	unit	Wireless 3x3 MU-MIMO Dual Band Gigabit Router		
			Processor: 1.2GHz Single-Core CPU; Ethernet Ports: 1 x Gigabit WAN Port, 4 x Gigabit Lan Ports; USB Support: 1 x USB 2.0 Port, Supported Partition Formats: NTFS, HFS+, FAT32, Supported Functions: FTP Server, Media Server, Samba Server		
			Power: 12V/1.5A, Antenna: 4 Fixed High-Performance Antennas(External and Internal) Beamforming		
			Wireless Standards: Wi-Fi5 IEEE 802.11ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz; Speed: 5GHz: 1300Mbps (802.11ac) 2.4GHz: 600Mbps (802.11n); WiFi Range: 3 Bedroom Houses; Working Modes: Router Mode, Access Mode; WiFi Encryption: WEP, WPA, WPA2, WPA/WPA2-Enterprise(802.1x); Network Security: SPI Firewall, Access Control, IP&MAC Binding, Application Layer Gateway; Guest Network: 1 x 5GHz Guest Network, 1 x 2.4GHz Guest Network; VPN Server: OpenVPN, PPTP; Protocols: IPv4, IPv6; Parental Controls: URL Filtering, Time Controls; WAN Types: Dynamic IP, Static IP, PPP0E, PPTP, L2TP; Quality of Service: QoS by Device; Cloud Service: OTA Firmware Upgrade, TP-Link ID, DDNS; NAT Forwarding: Port Forwarding, Port Triggering, DMZ, UPnP; IPTV: IGMP Proxy, IGMP Snooping, Bridge, Tag VLAN; DHCP: Address Reservation, DCHP Client List, Sever; DDNS: TP-Link, NO-IP, DynDNS; Management: Tether App, Webpage		
			At least 2 years warranty on parts and labor.		
10	4	unit	24-Port Gigabit Easy Smart Switch		

	Telephone nos. :	
	Company Name :	(Signature Over Frinces Hame)
	Authorized Company Representative:	(Signature Over Printed Name)
		PRICES IN THE ABOVE OFFER ARE CERTIFIED TRUE AND CORRECT:
	See And Sees, this Court (Sud)	
	And the Management	
	St. 1 Made	
	1017	AL
At least 2 years warranty		
Rate Limit, Storm Control Aggregation, Port Mirror VLAN: Supports up to 128	I; L2 Features: IGMP Snooping V1/V2/V3, Lin ing, Cable Diagnostics, Loop Prevention; 8 VLANs simultaneously (out of 4K VLAN IDs)	k
48Gbps; Packet Forwardi Packet Buffer Memory: 5	ng Rate: 35.7Mpps; MAC Address Table: 8K; 12KB; Jumbo Frame: 9KB; Quality of Service	
STP (maximum 100m); Fa 240VAC, 50/60Hz; Power	n Quality: Fanless; Power Supply: 100- Consumption: Maximum: 14.86W	
(maximum 100m), 100BA 100m), EIA/TIA-568 100Ω	SE-TX: UTP category 5, 5e cable (maximum STP (maximum 100m), 1000BASE-T: UTP	
AUTO Negotiation/AUTO	Interface: 24 10/100/1000Mbps RJ45 Ports MDI/MDIX; Network Media: 10BASE-T: UTP iximum 100m), EIA/TIA-568 100Ω STP	00000
	AUTO Negotiation/AUTO category 3, 4, 5 cable (maximum 100m), 100BA 100m), EIA/TIA-568 100Ω category 5, 5e, 6 or above STP (maximum 100m); Fa 240VAC, 50/60Hz; Power (220V/50Hz); Mounting: 48Gbps; Packet Forwardi Packet Buffer Memory: 5 Support Port-based/802. Rate Limit, Storm Contro Aggregation, Port Mirror VLAN: Supports up to 12: MTU/Port/Tag VLAN; Tra	AUTO Negotiation/AUTO MDI/MDIX; Network Media: 10BASE-T: UTP category 3, 4, 5 cable (maximum 100m), EIA/TIA-568 100Ω STP (maximum 100m), 100BASE-TX: UTP category 5, 5e cable (maximum 100m), 100BASE-TX: UTP category 5, 5e cable (maximum 100m), EIA/TIA-568 100Ω STP (maximum 100m), EIA/TIA-568 100Ω STP (maximum 100m), EIA/TIA-568 100Ω STP (maximum 100m); Fan Quality: Fanless; Power Supply: 100-240VAC, 50/60Hz; Power Consumption: Maximum: 14.86W (220V/50Hz); Mounting: Rack Mountable; Switching Capacity: 48Gbps; Packet Forwarding Rate: 35.7Mpps; MAC Address Table: 8K; Packet Buffer Memory: 512KB; Jumbo Frame: 9KB; Quality of Service Support Port-based/802.1p/DSCP priority, Support 4 priority queues, Rate Limit, Storm Control; L2 Features: IGMP Snooping V1/V2/V3, Lin Aggregation, Port Mirroring, Cable Diagnostics, Loop Prevention; VLAN: Supports up to 128 VLANs simultaneously (out of 4K VLAN IDs) MTU/Port/Tag VLAN; Transmission Method: Store-And-Forward  At least 2 years warranty on parts and labor.  TOTA  150,360.00  ediate  am-5:00pm  n 30 days  Authorized Company  Representative:  Company Name:  Address:  arly.  Uivalent, specify  Telephone nos.: